

TFS-1181

Intelligent Addressable Sounder with Built-in Isolator



Teknim TFS-1181 is an internal usage fire alarm sounder and can connect directly to loop line. It can be powered by loop line and has built-in isolator to protect the loop against shortcuts.

TFS-1181 has aesthetic design and low power consumption and are suitable for use with all Teknim addressable fire alarm control panels.

GENERAL FEATURES

- EN54-3 and EN54-17 Certified
- Built-in Isolator
- 97dB Sound level
- 42 Different Sound Tone
- 3 Different Sound Level Options
- IP21C protection class
- Red/White, transparent UL94 non-flammable poly-carbonate plastic frame

| Technical Specifications | TFS-1181 |
|--------------------------|--|
| Standard | EN54-3 and EN54-17 |
| Power | 15VDC – 32VDC (Norm.27VDC) |
| Average Consumption | ~90µA (@ 27VDC) |
| Alarm Consumption | Min.: 5.16mA, Norm.: 7.86mA, Max.: 11.23mA. |
| Sounder Type | Type A |
| Sound Level | Min: 89.4dB / Norm: 94.3dB / Max: 97dB ±2 dB (@27VDC, 1mt) |
| Usage | Internal |
| Dimensions (mm) | Ø110, h:55 mm |
| Weight | 27.7gr |
| Body Material | Red, UL94 anti- flammable ABS plastic |
| Operating Temperature | -10°C ~ 55°C |
| Humidity | 95% RH |
| Protection Class | IP21C |