

DC-D4216WRX 2.8mm

Full HD Vandal-Resistant IR Dome Camera



- Easy installation with DirectIP NVR
- micro SD/SDHC/SDXC
- IK10 / IP67 supports
- True wide dynamic range (WDR)
- Supports ONVIF
- Full HD (1080p) resolution
- Two-way audio
- PoE (IEEE 802.3af Class 2)
- IR LED (30m / 98.4 ft (4ea))
- Fixed-focal lens (f=2.8mm)
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	2.8mm
Aperture	F2.0
Iris Control	Fixed Iris
Angular Field of View	111.6°(H), 61.45°(V), 127.3°(D)
Min. Illumination	COLOR: 0.1 lux @ F2.0 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Pan/Tilt/Rotate	
Pan Range	-170° ~ 170°
Tilt Range	-5° ~ 67.5°
Rotate Range	-109° ~ 109°
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	30fps : 1920 x 1080 (WDR)
Supported Resolution	1920x1080, 1280x720, 640x360, 352x240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTSP/RTSP/HTTP/TCP, RTSP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SFTP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1X/EAP-TLS, Chained Fingerprint, SSLEncryption, HTTPSEncryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE IEEE802.3af (Class 2)
Power Consumption	PoE IEEE802.3af (Class 2), 4.6W
Approval	FCC CE KC
Mechanical	
Dimensions	Ø120.6 x 92.9mm (Ø4.75" x 3.65")
Weight	0.465kg (1.02lb)



PRODUCT IMAGE























DIMENSIONS



ACCESSORIES (OPTIONAL)



ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION	
DC-D4216WRX 2.8mm	WALL	 JUNCTION BOX Model:DA-JB4700	
		or	
		 MOUNT ADAPTER Model:DA-MA4300	
		+	
		 WALL MOUNT Model:DA-WM2050	
		 JUNCTION BOX Model: DA-JB4700	
	CELLING	or	
		 MOUNT ADAPTER Model: DA-MA4300	
		+	
		 CEILING MOUNT Model: DA-CM2050	
		POLE	 MOUNT ADAPTER Model: DA-MA4300
			+
	 WALL MOUNT Model: DA-WM2050		
	+		
	 POLE MOUNT Model: DA-LM2000		
	or		
	 JUNCTION BOX Model: DA-JB4700		
	+		
	 POLE MOUNT Model: DA-LM2000		
	or		
	 JUNCTION BOX Model: DA-JB4600		
	+		
	 POLE MOUNT Model: DA-LM2000		
	CORNER	 MOUNT ADAPTER Model:DA-MA4300	
+			
 WALL MOUNT Model:DA-WM2050			
+			
 CORNER MOUNT Model:DA-RM2000			
or			
 JUNCTION BOX Model:DA-JB4700			
+			
 CORNER MOUNT Model:DA-RM2000			
or			
 JUNCTION BOX Model:DA-JB4600			
+			
 CORNER MOUNT Model:DA-RM2000			