

DC-T4218WRA 2.8mm

H.265 2MP AI Bullet Camera (LightMaster NIR)



- 2MP (1920 x 1080) resolution
- NIR Sensor
- Easy installation with DirectIP NVR
- IK10, IP67
- micro SD/SDHC/SDXC
- IDIS Deep-Learning Analytics (IDLA)
- Day and night (ICR)
- H.265 and Intelligent Codec
- Alarm in / out
- Supports ONVIF
- IR LED (30 m / 98.4 ft (4 ea))
- True wide dynamic range (WDR)
- PoE (IEEE 802.3af Class 3)
- Audio in / out

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	2.8mm
Aperture	F1.6
Iris Control	Fixed Iris
Angular Field of View	105.8°(H),56.4°(V),121.2°(D)
Min. Illumination	COLOR: 0.1 lux @ F1.6 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30 m / 98.4 ft (4 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness Contrast, Colors, Brightness Control)
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Object Metadata : Human, Vehicle, Face IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection ETC Video Motion Detection, Active Tampering Alarm
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	60ips : 1920 x 1080 30ips : 1920 x 1080(WDR)
Supported Resolution	1920x1080, 1280x720, 640x360, 352x240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTSP, RTP, SPTCP, RTSP, RTSP, PHTP, TCP, RTP, UDP, RTSP, SPTCP, HTTP, HTTPS, FTP, S/NTP, S/MTP, FEN, mDNS, Upnp, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1X (EAP-TLS), Chained Fingerprint, SSLEncryption, HTTPSEncryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE IEEE802.3af (Class 3)
Power Consumption	PoE IEEE802.3af (Class 3), 8.2W
Approval	FCC CE KC
Mechanical	
Dimensions	81.5mm x 75mm x 200.5mm (3.21" x 2.95" x 7.89")
Weight	0.75kg (1.65 lb)



PRODUCT IMAGE













DIMENSIONS



ACCESSORIES (OPTIONAL)



ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-T4218WRA 2.8mm	WALL	 JUNCTION BOX Model: DA-JB4150
		or
		 JUNCTION BOX Model: DA-JB2400
	POLE	 POLE MOUNT Model: DA-LM2000
		+
		 JUNCTION BOX Model: DA-JB2400
		or
		 JUNCTION BOX Model: DA-JB4150
		+
	 POLE MOUNT Model: DA-LM2000	
	CORNER	 JUNCTION BOX Model: DA-JB4150
		+
 CORNER MOUNT Model: DA-RM2000		
or		
 CORNER MOUNT Model: DA-RM2000		
+		
 JUNCTION BOX Model: DA-JB2400		